



TAF CASE 900M

 1.178 x 780 x 330 mm, AUßENMAß / OUTER DIMENSION

 1.090 x 680 x 280 mm, INNENMAß / INNER DIMENSION

 70 + 210 mm TIEFE DECKEL-BODEN / DEPTH LID-BOTTOM

 GEWICHT LEER: 17,5 kg / WEIGHT EMPTY: 17,5 kg



Produktnummer / Product number
Leer / Empty: 100005636



- FASSUNGSVERMÖGEN: 215 LITER / VOLUME CAPACITY: 215 l
- STÜCK PRO KARTON: 1 / PCS PER CARTON: 1
- GEWICHT DES VOLLEN KARTONS: 21 KG / WEIGHT OF THE FULL CARTON: 21 KG
- GUSSFORM: SPRITZGUSS / MOULDING: INJECTION MOLDED
- TEMPERATURBEREICH: -51 bis 90°C / RANGE TEMPERATURE: -51 to 90°C
- ZUBEHÖR: VORHÄNGESCHLOSS / ACCESSORIES: PADLOCK
- GROßER KLAPPGRIF / LARGE FOLD DOWN HANDLE
- ROLLEN MIT ACHSEN AUS ROSTFREIEM STAHL / ROLLERS WITH STAINLESS STEEL AXLES
- SCHUTZART: IP67 ZERTIFIZIERT / PROTECTION TYPE: IP67 CERTIFIED

- UMLAUFENDE GUMMIDICHTUNG / SURROUNDING RUBBER SEAL
- DRUCKAUSGLEICHSSVENTIL / AUTOMATIC PRESSURE RELEASE VALVE
- 2-STUFIGE LONG LIFE KLIPPVERSCHLÜSSE / 2-STAGE LONG LIFE CLIP LOCK
- 4-FACH GELAGERTER TRAGEGRIF / 4-FOLD CARRYING HANDLE
- STAPELBAR / STACKABLE
- DICKES SCHALENMATERIAL / THICK BODY MATERIAL
- ZUSÄTZLICHE BEFESTIGUNGSPUNKTE / EXTRA FIXING POINTS
- NYLONSTIFTE, KORROSIONSFREI / NYLON PINS, CORROSION FREE
- SIEBDRUCK UND ETIKETTENFLÄCHE / SCREEN PRINTING AND LABEL SPACE
- MATERIAL: POLYPROPYLEN-COPOLYMER / MATERIAL: POLYPROPYLEN-COPOLYMER
- VERSCHLÜSSE: NYLON / LATCHES: NYLON
- O-RING: POLYMER / O-RING: POLYMER